Amendments To The Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of claims:

- 1. (Original) An optical data recording medium comprising a transparent substrate, a thin film layer formed on the transparent substrate and a protective film which is mainly comprised of a resin and formed on the thin film layer for protecting the thin film layer, wherein the thin film layer is a single layered or multilayered film including at least any one of a dielectric film, a recording film and a reflective film, and an expansion coefficient under humidity [ratio of expansion (1/%) where a difference of relative humidity (vapor content/saturated vapor amount at 25°C) is increased by 1%] of the protective film is greater than that of the transparent substrate and smaller than $1.7 \times 10^{-4} (1/\%)$.
 - 2. (Cancelled).
- 3. (Presently Amended) An optical data recording medium according to any one of elaims 1 and 2 claim 1, wherein a thickness of the protective film is 5 μ m or more to 20 μ m or less.
- 4. (Original) An optical data recording medium according to claim 1, wherein the expansion coefficient under humidity of the protective film is 7 or less times as great as that of the transparent substrate, the expansion coefficient under humidity being greater than 7×10^{-6} (1/%) and smaller than 5×10^{-5} (1/%).
- 5. (Presently Amended) An optical data recording medium according to any one of elaims 1 and 2claim 1, wherein the transparent substrate is made of a polycarbonate or a polyolefin and a thickness thereof is about 0.5 mm.

- 6. (Presently Amended) An optical data recording medium according to any one of claims 1 and 2 claim 1, wherein the protective film is made of an ultraviolet light curing resin.
- 7. (Original) A method of selecting a protective film in an optical data recording medium, the optical data recording medium comprising a transparent substrate, a thin film layer formed on the transparent substrate and the protective film which is mainly comprised of a resin and formed on the thin film layer for protecting the thin film layer, wherein, on condition that the thin film layer is a single layered or multilayered film including at least any one of a dielectric film, a recording film and a reflective film and the transparent substrate is made of a polycarbonate or a polyolefin with a thickness of 0.5 mm, the protective film is selected such that an expansion coefficient under humidity thereof (ratio of expansion (1/%) where a difference of relative humidity (vapor content/saturated vapor amount at 25°C is increased by 1%) is greater than that of the transparent substrate and smaller than $1.7 \times 10^{-4} (1/\%)$.
 - 8. (Cancelled).
- 9. (Presently Amended) An optical data recording medium provided with a protective film for protecting a thin film layer selected by the method of claim 7-or 8.